

BEDHEAD RECESSED

ANTI LIGATURE RANGE



- IP54 – IK10++
- Anti – Ligature *(See Note Below)
- 70mm Recess Depth
- Robust Mild Steel Facia
- Opal or Clear Reeded Polycarbonate Diffuser
- Stainless Steel Torx Security Screw Fix
- Compact Fluorescent or LED versions
- Other RAL Colour options



DESCRIPTION

Robust anti - ligature recessed bedhead luminaire with either compact fluorescent lamps or 7.2 watt LED array and 220 – 240 volt 50Hz electronic driver.

Luminaire can also be made suitable for exterior applications. Details on request.

APPLICATION

General Hospitals, Care Homes, Psychiatric Hospitals, Corridors, Amenity Low Level Lighting etc

***NOTE**

Only considered Anti - Ligature when correctly installed recessed in wall & using recommended 'Anti Pick' Mastic.

RANGE AVAILABLE

Catalogue No.

BHR113
BHR118

BHR7.2

Suffix

/O
/P
/W
/B
/SD

*Other RAL colours available

*External info on request.

Description

1x13w HF TC-DEL
1x18w HF TC-DEL

7.2w LED & Driver

Opal Polycarbonate Diffuser
Clear Reeded Polycarbonate Diffuser
White Paint Finish
Black Paint Finish
Security Key

Weight (Kg)

3.5 Kg
3.5 Kg

3.5 Kg

Dimensions

