

COMMANDER SMALL



AMENITY / MAINS AND EMERGENCY LIGHTING RANGE



- IP65 – IK10 ++
- Fully Welded Metal Base
- Opal or Clear Reeded Polycarbonate Diffuser
- Removable Gear Tray
- Stainless Steel Torx Captive Screw
- Conduit BESA Fixing
- Recessed Flange Version Optional
- LED Option



DESCRIPTION

Rectangular slim design. Bulkhead luminaire with 4 No Torx stainless steel screws. Removable high frequency gear tray for low energy fluorescent lamps, maintained & non maintained emergency versions. Conduit entry. Recessed version available.

APPLICATION

Interior & Exterior usage, Lobbies, Corridors, Multi Storey Car Parks, Stairs, Toilets etc

RANGE AVAILABLE

Catalogue No.

COMS108
COMS208
COMS108N3
COMS208N3
COMS108M3
COMS208S3

Suffix

/W
/B
/PC
/O
/P
/RM
/SS
/SD

COMS 18w LED/O

Description

1x8w HF T5 240V mains bulkhead
2x8w HF T5 240V mains bulkhead
1x8w HF T5 3 hour non-maintained bulkhead
2x8w HF T5 3 hour non-maintained bulkhead
1x8w HF T5 3 hour maintained bulkhead
2x8w HF T5 3 hour sustained bulkhead


White Metal Work
Black Metal Work
Integral Photozell
Opal Diffuser
Clear Reeded Diffuser
Recess Mount option cut out 380mm x 155mm
Security Screws
Security Driver

18w LED (Opal Diffuser)

Weight (Kg)

2.5 Kg
2.5 Kg
3.0 Kg
3.0 Kg
3.0 Kg
3.0 Kg

Dimensions



Cut out 380mm x 155mm
Recessed version

