

GLADIATOR ANGLE



VANDAL RESISTANT SURFACE FLUORESCENT RANGE



- IP54 – IK10
- Fully Welded Construction
- Clear Reeded Polycarbonate Dish Diffuser
- Vandal Resistant Design
- Removable High Frequency Gear Tray
- Stainless Steel Security Screws
- Various RAL Colour Options



DESCRIPTION

A range of resilient vandal resistant luminaires. The body is fabricated fully welded sheet steel. The drop dish diffuser is made from tough polycarbonate and is held captive with side rails and stainless steel security screws. The high frequency gear tray is fully removable and acts as a reflector.

APPLICATION

Medium Security Areas, Pedestrian Walk Ways, Car Parks, Schools, Public Areas, Local Authority Areas etc

RANGE AVAILABLE

Catalogue No.	Description	Length	Weight (Kg)	Dimensions
GLRA114	1x14w HF T5	2ft / 650mm	5 Kg	
GLRA128	1x28w HF T5	4ft / 1250mm	8 Kg	
GLRA154	1x54w HF T5	4ft / 1250mm	8 Kg	
GLRA135	1x35w HF T5	5ft / 1550mm	9 Kg	
GLRA149	1x49w HF T5	5ft / 1550mm	9 Kg	
GLRA214	2x14w HF T5	2ft / 650mm	5 Kg	
GLRA228	2x28w HF T5	4ft / 1250mm	8 Kg	
GLRA254	2x54w HF T5	4ft / 1450mm	8 Kg	
GLRA235	2x35w HF T5	5ft / 1550mm	9 Kg	
GLRA249	2x49w HF T5	5ft / 1550mm	9 Kg	
Suffix				
/HFD	High Frequency Dimmable Gear			
/EM3	3 Hour Integral Maintained Emergency			
/W	White Paint Finish			
/B	Black Paint Finish			
/SD	Security Driver			

*Other RAL colours on request

*Stainless Steel version for special applications