



MAYFAIR ROUND DISH

AMENITY LIGHTING



IP65

IK10

- IP65 – IK10
- Polycarbonate Body & Diffuser
- Wall, Ceiling or Recessed Mount
- Removable Hinged High Frequency Gear Tray
- Opal or Clear Prismatic Diffuser
- White or Black Base



DESCRIPTION

All polycarbonate enclosure fitted with Pozi – drive Diffuser fixing screws as standard. Torx security screws optional. Facility for side entry conduit. Semi-Recess Kit available as optional extra.

APPLICATION

Amenity areas, Lobbies, Corridors, Store Rooms, General Areas.

Catalogue No.

MAYR162D
MAYR282D
MAYR382D

Suffix

/W
/B
/DP
/DO
/PC
/SS
/SD
/EM3
/RC-KIT

Description


16w 2D HF TC-DD
28w 2D HF TC-DD
38w 2D HF TC-DD

White Body
Black Body
Dish Prismatic Diffuser
Dish Opal Diffuser
Integral Photocell
Fitted with Security Screws
Security Screwdriver
3 hour Integral Emergency – (excluding 38w2D)
Semi - Recessing Kit cut out 290mm Ø

Weight (Kg)

1.5 Kg
1.5 Kg
1.5 Kg

Dimensions



Cut out Ø 290mm
Recessed version

