

PLATOON



VANDAL RESISTANT AMENITY LIGHTING



- IP65 – IK10 ++
- Fabricated Steel Body
- Surface & Recessed Versions
- Opal or Clear Prismatic Polycarbonate Diffuser
- Torx Security Screw Fixing
- Removable High Frequency Gear Tray
- 60° Ski - Slope Version For Surface Range
- Black or White Texture Paint Finish as Standard
- LED Option



DESCRIPTION

Shallow compact robust amenity luminaire with fully welded fabricated steel construction. Removable gear tray. Heavy duty polycarbonate diffuser available in clear prismatic or opal, fixed with 4 No resist torx stainless steel security screws.

APPLICATION

Public Spaces, Car Parks, Canopies, Subways, External Lighting, Public Authority etc

RANGE AVAILABLE

Catalogue No.

Description

Weight (Kg)

Dimensions

Surface Version

PLA162D	16w 2D HF TC-DD Surface Luminaire	4 Kg
PLA282D	28w 2D HF TC-DD Surface Luminaire	4 Kg
PLA382D	38w 2D HF TC-DD Surface Luminaire	4 Kg

Recessed Version – cut out 275mm x 275mm

PLAR162D	16w 2D HF TC-DD Recessed Luminaire	4 Kg
PLAR282D	28w 2D HF TC-DD Recessed Luminaire	4 Kg
PLAR382D	38w 2D HF TC-DD Recessed Luminaire	4 Kg

Suffix

/O	Opal Diffuser
/P	Prismatic Diffuser
/B	Black Paint Finish
/W	White Paint Finish
/PC	Integral Photocell
/EM3	3 hour integral Emergency
/SS	Security Screws
/SD	Security Screw Driver

60° 60° Ski-Slope For Surface Range

PLA/R 18w LED/O 18w LED (Opal Diffuser)



Cut out 275mm x 275mm
Recessed version

