




REFLEX 520

ANTI-LIGATURE SURFACE RANGE



- IP40/65 - IK10 ++
- Surface Mount Anti-Ligature Luminaire *(See note below)
- 520mm Diameter High Grade Aluminium Body
- Clear Prismatic or Opal Polycarbonate Diffuser
- Stainless Steel Security Screws
- Removable High Frequency Gear Tray
- Other RAL Colours Available
- Anodised Colour Finish Options
- LED Option



DESCRIPTION

Slim Profile circular surface luminaire. Spun aluminium 520 mm diameter body, captive opal or prismatic polycarbonate diffuser. Removable electronic high frequency gear tray. 5 No stainless steel torx security screws.

APPLICATION

Psychiatric Hospitals, Secure Unit, Schools, Toilets, Corridors, Public Buildings, Lobbies etc

*NOTE

Only considered Anti Ligature when correctly installed on ceiling & using recommended 'Anti Pick' Mastic.

RANGE AVAILABLE

Catalogue No.

Description

Weight (Kg)

Dimensions

RFXL282D
RFXL382D
RFXL218
RFXL226
RFXL140
RFXL155
RFXL22/55

1x28w 2D HF TC-DD
1x38w 2D HF TC-DD
2x18w HF TC-DEL
2x26w HF TC-DEL
1x40w HF T16R
1x55w HF T16R
1x22/55w HF T16R

5 Kg
5 Kg
5 Kg
5 Kg
5 Kg
5 Kg
5 Kg

Suffix

/HFD
/P
/O
/W
/EM3
/NL
/SD
/IP65

High Frequency Dimmable
Prismatic Diffuser
Opal Diffuser
White Paint Finish
Integral Maintained Emergency
Night Light
Security Driver
IP65 Gasket (optional)

*Other RAL colours available
*Anodised colour options available

/RFXL18wLED/0

18w LED (opal diffuser)

