

REFLEX RECESS



ANTI-LIGATURE RECESSED RANGE



- IP40/65 - IK10 ++
- Recess Mount Anti-Ligature Luminaire *(See Note Below)
- 335mm Diameter High Grade Aluminium Body
- Clear Prismatic or Opal Polycarbonate Diffuser
- Stainless Steel Security Screws
- Removable High Frequency Gear Tray
- Other RAL Colours Available
- Anodised Colour Finish Options
- LED Option



DESCRIPTION

Recessed robust anti ligature sealed luminaire, captive opal or prismatic polycarbonate dish diffuser with 4 No Torx security screw fixing. 3 x Internal adjustable side arm suspension brackets. Electronic high frequency gear.

APPLICATION

Psychiatric Hospitals, Secure Unit Areas, Schools, Toilets, Corridors, Public Buildings, Lobbies etc

*NOTE

Only considered Anti Ligature when correctly installed on ceiling & using recommended Anti Pick' Mastic.

RANGE AVAILABLE

Catalogue No.

Description

Weight (Kg)

Dimensions

RFXR162D
RFXR282D
RFXR382D

1x16w 2D HF TC-DD
1x28w 2D HF TC-DD
1x38w 2D HF TC-DD

4 Kg
4 Kg
4 Kg

RFXR218
RFXR226

2x18w HF TC-DEL
2x26w HF TC-DEL

4 Kg
4 Kg

RFXR22

1x22w HF T5 (T16R)

4 Kg

Suffix

/HFD
/P
/O
/W
/EM3
/NL
/SD
/IP65

High Frequency Dimmable
Prismatic Diffuser
Opal Diffuser
White Paint Finish
Integral Maintained Emergency
Night Light
Security Driver
IP65 Gasket (optional)

*other RAL colours available
*Anodised colour options available

/RFXR18wLED/0

18w LED (opal diffuser)



Cut out Ø 270mm

