



# SECURITY LOUVRE

## RECESSED MODULAR RANGE



- IP65 – IK10++
- Steel Body Powder Coated White
- Suitable for Concealed or Exposed T25'Grid Ceilings
- Fully Gasketed Regressed Frame
- Captive Clear Polycarbonate Panel
- Removable High Frequency Gear Tray
- Polished Anodised Aluminium Low Brightness Louvre
- Stainless Steel Security Screws



### DESCRIPTION

Robust recessed mounted enclosed luminaire with white paint finish. Clear polycarbonate panel with aluminium low brightness louvre, traditional ceiling construction supplied c/w 4 x No adjustable side arm suspension brackets. Underside body rated IP65.

### APPLICATION

Prisons, Police Stations, Detention Centres, Secure Units, Hospitals, Schools, Offices, Kitchens, Laboratories, Clean Rooms etc

### RANGE AVAILABLE

| Catalogue No. | Description                     | Dimension (mm) | Weight (Kg) | Dimensions |
|---------------|---------------------------------|----------------|-------------|------------|
| SCRL214       | 2x14w HF T5                     | 600mmx300mm    | 6 Kg        |            |
| SCRL224       | 2x24w HF T5                     | 600mmx300mm    | 6 Kg        |            |
| SCRL314       | 3x14w HF T5                     | 600mmx600mm    | 10 Kg       |            |
| SCRL414       | 4x14w HF T5                     | 600mmx600mm    | 10 Kg       |            |
| SCRL228       | 2x28w HF T5                     | 1200mmx300mm   | 9 Kg        |            |
| SCRL224       | 2x54w HF T5                     | 1200mmx300mm   | 9 Kg        |            |
| SCRL328       | 3x28w HF T5                     | 1200mmx600mm   | 14 Kg       |            |
| SCRL428       | 4x28w HF T5                     | 1200mmx600mm   | 14 Kg       |            |
| SCRL354       | 3x54w HF T5                     | 1200mmx600mm   | 14 Kg       |            |
| SCRL454       | 4x54w HF T5                     | 1200mmx600mm   | 14 Kg       |            |
| <b>Suffix</b> |                                 |                |             |            |
| /P            | Clear Obscure Diffuser          |                |             |            |
| /O            | Opal Diffuser                   |                |             |            |
| /L2           | Aluminium CAT2 Louvre           |                |             |            |
| /HFD          | High Frequency Dimmable Gear    |                |             |            |
| /EM3          | 3 hr Maintained Emergency       |                |             |            |
| /NL           | Night Light                     |                |             |            |
| /SS           | Stainless Steel Security Screws |                |             |            |
| /SD           | Security Driver                 |                |             |            |