

SECURITY



RECESSED MODULAR RANGE



- IP65 – IK10++
- Steel Body Powder Coated White
- Suitable for Concealed, Exposed Grid Ceilings & Spring T
- Fully Gasketed Regressed Frame
- Captive Polycarbonate Diffuser
- Clear Stippled or Opal Panel
- Stainless Steel Security Screws
- Removable High Frequency Gear Tray



DESCRIPTION

Robust recessed mounted enclosed luminaire with white paint finish. Traditional ceiling construction supplied c/w 4 x No adjustable side arm suspension brackets. Underside body rated IP65.

APPLICATION

Prisons, Police Stations, Detention Centres, Hospitals, Schools, Secure Units, Kitchens, Laboratories, Clean Rooms etc

RANGE AVAILABLE

Catalogue No.	Description	Dimension (mm)	Weight (Kg)	Dimensions
SCR214	2x14w HF T5	600mmx300mm	6 Kg	
SCR224	2x24w HF T5	600mmx300mm	6 Kg	
SCR314	3x14w HF T5	600mmx600mm	10 Kg	
SCR414	4x14w HF T5	600mmx600mm	10 Kg	
SCR228	2x28w HF T5	1200mmx300mm	9 Kg	
SCR224	2x54w HF T5	1200mmx300mm	9 Kg	
SCR328	3x28w HF T5	1200mmx600mm	14 Kg	
SCR428	4x28w HF T5	1200mmx600mm	14 Kg	
SCR354	3x54w HF T5	1200mmx600mm	14 Kg	
SCR454	4x54w HF T5	1200mmx600mm	14 Kg	
Suffix				
/P	Clear Obscure Diffuser			
/O	Opal Diffuser			
/HFD	High Frequency Dimmable Gear			
/EM3	3 hr Maintained Emergency			
/NL	9 watt Night Light			
/SS	Stainless Steel Security Screws			
/SD	Security Driver			