



SKYE POST TOP

EXTERIOR LIGHTING RANGE



- IP65 – IK10++
- Non Corrosive Vandal Resistant
- 5 mm Thick Clear Reeded Polycarbonate Visor
- Integral Gear Tray c/w Easy Access Connections
- Integral Photo Cell (optional)
- To Fit 76mm Ø Post
- NEMA Socket option
- Large Canopy Top Hat (optional)
- Moulded Black Poly Prop Base & Lid



DESCRIPTION

Extremely tough black Poly Prop heavy duty base & lid with 76 mm diameter spigot entry. Integral control gear. Optional Large black top hat canopy to reduce upward light content. Optional inner 180° light shield.

APPLICATION

Vandal Resistant Areas, Parks, Drives, Roadways, Coastal Regions, Saline Atmospheres, Housing Estates, Access Roads, Car Parks.

RANGE AVAILABLE

Catalogue No.

SKY50S
SKY70S
SKY100S

SKY50MH
SKY70MH

Suffix

/PC
/PS
/SKY.CAN
L/Shield

*Refer to page 48 for spigot adapters

Description

50w SON
70w SON
100w SON

50w HIPE
70w HIPE

Mini Photo-Cell
NEMA photocell socket only
Black Top Canopy 520 diameter
180° Inner Light Shield

Weight (Kg)

4.5 Kg
4.5 Kg
4.5 Kg

4.5 Kg
4.5 Kg

Dimensions

