



TITAN III

(SAFER CELL) ANTI LIGATURE CORNICE RANGE



- *NOMS STD/E/SPEC/022/Cellular & Safer Cell Accommodation
- IP65 - IK10 ++
- Anti Ligature *(See Note Below)
- Fully Welded Fabricated Steel Body Cornice Luminaire
- Regressed Gasketted Bezel
- Captive Diffuser Panel
- 3 x Compartment Cable Tray
- Torx Security Screw
- Removable High Frequency Gear Tray
- LED Option



DESCRIPTION

A range of vandal resistant, anti ligature luminaires. The fittings are 'anti ligature' for use in sensitive areas & designed to run 'wall to wall' and can be adjusted in length. Can be supplied as individual/stand alone fittings.

APPLICATION

For use in Prison 'Safer Cell' and sensitive areas, Police Stations, Public Areas where a high degree of vandal resistance is required. Manufactured to length to suit application.

*NOTE

Only considered Anti - Ligature when correctly installed against wall & ceiling and using recommended 'Anti Pick' Mastic.

RANGE AVAILABLE

Catalogue No.	Description	Dimension (mm)	Weight (Kg)	Dimensions
TTNN114	1x14w HF T5	2ft/ 730mm	12 Kg	
TTNN128	1x28w HF T5	4ft/ 1430mm	18 Kg	
TTNN135	1x35w HF T5	5ft/ 1730mm	22 Kg	
TTNN149	1x49w HF T5	5ft/ 1730mm	22 Kg	
TTNN154	1x54w HF T5	4ft/ 1430mm	18 Kg	
TTNN214	2x14w HF T5	2ft/ 730mm	12 Kg	
TTNN228	2x28w HF T5	4ft/ 1430mm	18 Kg	
TTNN235	2x35w HF T5	5ft/ 1730mm	22 Kg	
TTNN249	2x49w HF T5	5ft/ 1730mm	22 Kg	
TTNN254	2x54w HF T5	4ft/ 1430mm	18 Kg	
*TTNN128/154/7	1x28/1x54w&1x7w Night Light <i>{Safer cell requirement} Dimensions tbc (further info on request)</i>			
Suffix				
/O	Opal Diffuser			
/P	Clear Stippled Diffuser			
/GRP	Glass Reinforced Panel			
/EM3	3 Hour Maintained Emergency			
/NL	Night Light			
/SD	Security Driver			