

V-LEXX



SURFACE FLUORESCENT RANGE



- IP44 – IK10
- Clear Prismatic Polycarbonate Controller
- Polycarbonate End Cap
- Removable High Frequency Gear Tray
- Stainless Steel Security Torx Screws (optional)
- White Metal Work



DESCRIPTION

Surface mounted enclosed luminaire with 3 mm prismatic polycarbonate diffuser, injection moulded polycarbonate end-caps, can be fixed with optional stainless steel security screw. Removable high frequency gear tray.

APPLICATION

School Classroom, Corridors, Offices, Public Spaces & Care Homes.

RANGE AVAILABLE

Catalogue No.	Description	Length	Weight (Kg)	Dimensions
VDX114	1x14w HF T5	2ft/ 600 mm	2.5 Kg	
VDX128	1x28w HF T5	4ft/1200 mm	3.5 Kg	
VDX154	1x54w HF T5	4ft/1200 mm	3.5 Kg	
VDX135	1x35w HF T5	5ft/1500 mm	4.0 Kg	
VDX149	1x49w HF T5	5ft/1500 mm	4.0 Kg	
VDX214	2x14w HF T5	2ft/ 600 mm	2.5 Kg	
VDX228	2x28w HF T5	4ft/1200 mm	3.5 Kg	
VDX254	2x54w HF T5	4ft/1200 mm	3.5 Kg	
VDX235	2x35w HF T5	5ft/1500 mm	4.0 Kg	
VDX249	2x49w HF T5	5ft/1500 mm	4.0 Kg	
Suffix				
/HFD	Dimmable			
/P	Prismatic Polycarbonate Diffuser			
/NL	Night Light			
/EM3	3 hr Maintained Emergency			
/SD	Security Screw			