


# V-LEXX ANGLE SECURE



- IP44/54 – IK10++
- Metal End Cap
- Clear Prismatic Polycarbonate Controller
- Vandal Resistant Design
- Stainless Steel Security Screws
- Removable High Frequency Gear-Tray
- White Metalwork Standard
- Other RAL Colour Options



## DESCRIPTION

A shallow cornice mounted robust luminaire incorporating a clear reeded extruded polycarbonate diffuser, supported along its length by the luminaire body & held captive by die cast aluminium end cap. Fixed by stainless steel security screws. Removable high frequency gear tray. Standard luminaire IP44, optional gasket to IP54

## APPLICATION

Car Parks, Medium Security Areas, Pedestrian Walk Ways, Schools, Public Areas, Local Authority Areas etc

## RANGE AVAILABLE

Catalogue No.	Description	Length	Weight (Kg)	Dimensions
VDXA114	1 x 14w/HF/T5	2ft/ 600mm	4.0 Kg	
VDXA128	1 x 28w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA154	1 x 54w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA135	1 x 35w/HF/T5	5ft/1500mm	8.0 Kg	
VDXA149	1 x 49w/HF/T5	5ft/1500mm	8.0 Kg	
VDXA214	2 x 14w/HF/T5	2ft/ 600mm	4.0 Kg	
VDXA228	2 x 28w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA254	2 x 54w/HF/T5	4ft/1200mm	7.0 Kg	
VDXA235	2 x 35w/HF/T5	5ft/1500mm	8.0 Kg	
VDXA249	2 x 49w/HF/T5	5ft/1500mm	8.0 Kg	

### Suffix

/HFD	High Frequency Dimmable Gear
/EM3	3 hour Maintained Emergency
/NL	Night Lite
/SD	Security Key
/IP54	IP54 Version

\*Other RAL colours on request

\*Stainless Steel version available for special applications

080

VANDAL RESISTANT SURFACE FLUORESCENT RANGE