



VICTORY

CORROSION RESISTANT



- IP65
- Corrosion Resistant
- Polycarbonate Body & Clear Reeded Controller
- Removable High Frequency Gear Tray
- Optional Vandal Resistant Stainless Steel Diffuser Clips
- 20 mm Cable Entry End Holes c/w Sealing Plugs



DESCRIPTION

Industrial luminaire suitable for many arduous applications. Nylon toggle clips as standard, stainless steel security toggle clips (optional). Polycarbonate clear reeded controller. End wiring facility.

APPLICATION

Wash Rooms, Under Canopy, Warehouses, Boiler Rooms etc

RANGE AVAILABLE

Catalogue No.

Description


Weight (Kg)

Dimensions

VCT114
VCT128
VCT154
VCT135
VCT149

1x14w HF T5 2ft/ 666mm
1x28w HF T5 4ft/1276mm
1x54w HF T5 4ft/1276mm
1x35w HF T5 5ft/1576mm
1x49w HF T5 5ft/1576mm

1.9 Kg
2.9 Kg
2.9 Kg
3.8 Kg
3.8 Kg



VCT214
VCT228
VCT254
CT235
VCT249

2x14w HF T5 2ft/ 666mm
2x28w HF T5 4ft/1276mm
2x54w HF T5 4ft/1276mm
2x35w HF T5 5ft/1576mm
2x49w HF T5 5ft/1576mm

2.2 Kg
4.5 Kg
4.5 Kg
6.2 Kg
6.2 Kg



Suffix

/EM3
/VRC

3 hour Integral Maintained Emergency
Stainless Steel Vandal Resistant Clips