

## VANDAL RESISTANT SURFACE FLUORESCENT RANGE



- IP65 - IK10 ++
- Fully Welded Fabricated Steel Body Luminaire
- Regressed Gasketed Bezel
- Captive 6mm Opal or Clear Stippled Polycarbonate Diffuser
- Stainless Steel Torx Security Screw Fixing
- Removable High Frequency Gear Tray
- Other RAL Colour Options



### DESCRIPTION

Robust cornice mounted enclosed luminaire with white texture paint finish as standard, RAL colours Optional.

### APPLICATION

Corridors, Warehouses, Covered Walk Ways, Schools, Hospitals, Prisons, Police Stations, Public Areas, Underpass Walkways etc

### RANGE AVAILABLE

Catalogue No.	Description	Dimension (mm)	Weight (Kg)	Dimensions
WFD114	1x14w HF T5	2ft/ 660mm	5.0 Kg	
WFD124	1x24w HF T5	2ft/ 660mm	5.0 Kg	
WFD128	1x28w HF T5	4ft/1260mm	7.0 Kg	
WFD154	1x54w HF T5	4ft/1260mm	7.0 Kg	
WFD135	1x35w HF T5	5ft/1560mm	8.0 Kg	
WRD149	1x49w HF T5	5ft/1560mm	8.0 Kg	
WFD214	2x14w HF T5	2ft/ 660mm	5.0 Kg	
WFD224	2x24w HF T5	2ft/ 660mm	5.0 Kg	
WFD228	2x28w HF T5	4ft/1260mm	7.0 Kg	
WFD254	2x54w HF T5	4ft/1260mm	7.0 Kg	
WFD235	2x35w HF T5	5ft/1560mm	8.0 Kg	
WFD249	2x49w HF T5	5ft/1560mm	8.0 Kg	
<b>Suffix</b>				
/P	Clear Stippled Diffuser			
/O	Opal Diffuser			
/HFD	High frequency Dimmable			
/NL	Night Light			
/EM3	3 hour maintained emergency			
/SD	Security Driver			

\*Also available in stainless steel for special applications