

## VANDAL RESISTANT SURFACE FLUORESCENT RANGE



- IP65 – IK10++
- Fully Welded Fabricated Steel Body
- Regressed Gasketed Bezel
- Captive 6mm Opal or Clear Stippled Polycarbonate Panel
- Stainless Steel Torx Security Screw Fixing
- Removable High Frequency Gear Tray
- Other RAL Colour Options



### DESCRIPTION

Robust surface mounted enclosed luminaire, anti ligature construction with texture white paint finish as standard.

### APPLICATION

Pharmaceutical Environments, Hospitals, Secure Units, Kitchens, Laboratories, Clean Rooms etc

### RANGE AVAILABLE

Catalogue No.	Description	Dimension (mm)	Weight (Kg)	Dimensions
WYE314	3x14w HF T5	660mmx660mm	10 Kg	
WYE414	4x14w HF T5	660mmx660mm	10 Kg	
WYE324	3x24w HF T5	660mmx660mm	10 Kg	
WYE424	4x24w HF T5	660mmx660mm	10 Kg	
WYE328	3x28w HF T5	1200mmx600mm	14 Kg	
WYE428	4x28w HF T5	1200mmx600mm	14 Kg	
WYE354	3x54w HF T5	1200mmx600mm	14 Kg	
WYE454	4x54w HF T5	1200mmx600mm	14 Kg	
<b>Suffix</b>				
/P	Clear Stippled Diffuser			
/O	Opal Diffuser			
/HFD	High Frequency Dimmable Gear			
/EM3	3 hr Maintained Emergency			
/NL	Night Light			
/SD	Security Driver			

\*Stainless Steel version for special applications