



## VANDAL RESISTANT SURFACE FLUORESCENT RANGE



- IP65 – IK10 ++
- Fully welded Fabricated Steel Body
- Regressed Gasketed Bezel
- Captive 6mm Opal or Clear Stippled Polycarbonate Panel
- Torx Security Screw Fixing
- Removable High Frequency Gear Tray
- Other RAL Colour Options



### DESCRIPTION

Slim robust surface mounted enclosed luminaire, anti-ligature construction (when installed correctly) with texture white paint finish as standard.

### APPLICATION

Prisons, Police Stations, Detention Centres, Public Spaces, Psychiatric Hospitals, Schools etc

### RANGE AVAILABLE

Catalogue No.	Description	Length (mm)	Weight (Kg)	Dimensions
WYE114	1x14w HF T5	2ft/ 650mm	4.0 Kg	
WYE124	1x24w HF T5	2ft/ 650mm	4.0 Kg	
WYE128	1x28w HF T5	4ft/1250mm	6.0 Kg	
WYE154	1x54w HF T5	4ft/1250mm	6.0 Kg	
WYE135	1x35w HF T5	5ft/1550mm	7.0 Kg	
WYE149	1x49w HF T5	5ft/1550mm	7.0 Kg	
WYE214	2x14w HF T5	2ft/ 650mm	4.0 Kg	
WYE224	2x24w HF T5	2ft/ 650mm	4.0 Kg	
WYE228	2x28w HF T5	4ft/1250mm	6.0 Kg	
WYE254	2x54w HF T5	4ft/1250mm	6.0 Kg	
WYE235	2x35w HF T5	5ft/1550mm	7.0 Kg	
WYE249	2x49w HF T5	5ft/1550mm	7.0 Kg	
<b>Suffix</b>				
/HFD	High Frequency Dimmable			
/P	Clear Stippled Diffuser			
/O	Opal Diffuser			
/EM3	Integral 3 Hour Emergency.			
/NL	9w Night Light			
/SD	Security Key			

\*Stainless Steel Version for special applications